


Specifications

Eaton 9SX11KIRT4UG2



Eaton 9SX Gen2 UPS, 11000 VA, 11000 W,
Input: Hardwired, Outputs: (8) C13, (4) C19,
Hardwired, Rack/tower, 4U, Rack-mounting
kit included

Photo is representative



General specifications

PRODUCT NAME	Eaton 9SX Gen2 UPS
CATALOG NUMBER	9SX11KIRT4UG2
MODEL CODE	Eaton 9SX 11000i RT4U G2
EAN	3553340710704
PRODUCT LENGTH/DEPTH	725 mm
PRODUCT HEIGHT	174 mm
PRODUCT WIDTH	440 mm
PRODUCT WEIGHT	78.8 kg
WARRANTY	2 year
COMPLIANCES	LVD Directive (CB) EMC Directive RoHS Directive REACH WEEE Directive Packaging Directive Batteries Directive
CERTIFICATIONS	IEC/EN 62040-1 IEC/EN 62040-2 IEC/EN 62040-3 ENERGY STAR certified CE cULus UKCA Cm Ukr RCM KCC BSMI

Battery

BATTERY TYPE	Sealed, lead-acid
RUNTIME GRAPH	\$row.attributeValue.cdata
BATTERY REPLACEMENT	Hot-swappable internal batteries and extended battery modules (EBMs)
BATTERY QUANTITY	20
BATTERY MANAGEMENT	• ABM+ (Predictive battery life) & Temperature compensated charging method (user selectable) • Automatic battery test • Deep discharge protection • Automatic recognition of external battery units
BATTERY RATING	12 V / 7 Ah
EXTENDED BATTERY CAPABILITY	Yes

Electrical input

NOMINAL FREQUENCY	50/60 Hz
INPUT POWER FACTOR	>.99
INPUT VOLTAGE RANGE	176-276 V (100-276 V with derating)
INPUT FREQUENCY RANGE	40-70 Hz

Electrical output

RECEPTACLE	(8) C13, (4) C19, Hardwired
VOLTAGE	230V
VA RATING	11 kVA
WATTAGE	11 kW
OUTPUT POWER FACTOR	1
OUTPUT WAVEFORM	Sine wave
OUTPUT NOMINAL VOLTAGE	230V default (200/208/220/230/240V)
VOLTAGE DISTORTION OUTPUT (LINEAR LOAD) - MAX	1
FEED TYPE	1
TOPOLOGY	Online/Double-conversion

Communications

INCLUDES NETWORK CARD	No
COMMUNICATION	• USB port (HID compliant) • Serial port (RS232) • Mini terminal block for remote On/Off • Mini-terminal block for remote power off • Mini-terminal block for dry contacts outputs (2 contacts)
ETHERNET INTERFACE	No
USER INTERFACE	Multilingual graphical LCD display
POTENTIAL FREE SWITCH CONTACT	Yes
EXPANSION SLOTS	One slot
SOFTWARE COMPATIBILITY	Eaton Brighthouse Software suite

TYPE OF INTERFACE	Other
-------------------	-------

Environmental

ALTITUDE	3000 m
NOISE LEVEL	<37 dB at 1 meter
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)
RELATIVE HUMIDITY	0-95% non-condensing

Additional specifications

CONSTRUCTION TYPE	482.6 mm (19 inch) device
-------------------	---------------------------

PACKAGE CONTENTS

- UPS
- (3) cable glands
- (2) IEC-IEC output cables (1,2m)
- USB cable (1,8m)
- Cable locking systems
- Supports for tower mounting
- Rack-mounting kit with brackets and slides for UPS
- Safety instructions
- Quickstart guide

INTERNAL BYPASS	Yes
-----------------	-----

AUTO SHUTDOWN FUNCTION	Yes
------------------------	-----

COLOR	Black
-------	-------

EFFICIENCY AT MAX. LOAD	97
-------------------------	----

RACK MOUNTING KIT	Yes
-------------------	-----

HOT SWAP POWER	No
----------------	----

Resources

BROCHURES	Eaton 9SX Gen2 UPS Datasheet - EN
COMPLIANCE INFORMATION	Eaton single phase UPS Transportation document according to DGR
DECLARATIONS OF CONFORMITY	Eaton 9SX Gen2 Declaration of Conformity
MANUALS AND USER GUIDES	Eaton 9SX Gen2 UPS Advanced User Guide - EN
PEP ECO-PASSPORT	Eaton 9PX 9SX Gen2 UPS 5-6k VA PEP Ecopassport Eaton 9PX 9SX Gen2 UPS 8-11 kVA PEP Ecopassport

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

