

CAT. N° 4 097 85



## MCB - DX<sup>3</sup> - 25 KA - 3P 400 V~ - 40 A - C CURVE

|                           |        |
|---------------------------|--------|
| Pack (number of units)    | 1      |
| Volume (dm <sup>3</sup> ) | 1,04   |
| Weight (g)                | 680,00 |

### Product characteristics

#### 3-pole - 400 V~

- C curve
- Nominal rating I<sub>n</sub> : 40 A
- Number of modules : 4.5

### General characteristics

#### MCBs DX<sup>3</sup> - 25 kA - thermal magnetic MCBs from 2 A to 125 A - C and D curves

- Breaking capacity:
- 25 kA - IEC 60947-2 - 400 V~
- Can be equipped with DX<sup>3</sup> signalling and remote tripping auxiliaries and motorised controls

### Documentation



#### Catalogue pages & additional information

- [Description page \(p.068\)](#)
- [Technical page \(p.074-075\)](#)
- [Dimensions of din-rail equipment](#)
- [Performance of MCBs and auxiliaries](#)



#### Installation & technical data

- [F01217EN-01](#)



#### Environmental product profile

- [Environnemental product sheet n°8 E0084A-FR](#)
- [LGRP-00269-V01](#)



#### Installation instructions & related documents

- [LE03603AG](#)



#### Agreements & certificates of conformity

- [LOVAG-IT 13](#)