CAT. N° 4 097 82



MCB - DX³ - 25 KA - 3P 400 V~ - 20 A - C CURVE

Pack (number of units)	1
Volume (dm³)	0,716
Weight (g)	459,00

Product characteristics

3-pole - 400 V~

- C curve
- Nominal rating In : 20 A
- Number of modules : 3/4.5

General characteristics

MCBs DX³ - 25 kA - thermal magnetic MCBs from 2 A to 125 A - C and D curves

- Breaking capacity:
- 25 kA - IEC 60947-2 - 400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls

Documentation

Catalogue pages & additional information

- Description page (p.068)
- Technical page (p.074-075)
- Dimensions of din-rail equipment
- Performance of MCBs and auxiliaries

Agreements & certificates of conformity

- LOVAG-IT 13

Installation & technical data

- F01303EN-00

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.