CAT. N° 4 092 80



MCB - DX³ 10000 - 16 KA - 3P 400 V~ - 80 A - C CURVE

Pack (number of units)	1
Volume (dm³)	1,04
Weight (g)	705,00

Product characteristics

3-pole 400 V~

- C curve
- Nominal rating In : 80 A
- Number of modules : 4.5

General characteristics

MCBs DX³ 10000 - 16 kA - thermal magnetic circuit breakers from 1 A to 125 A - B and C curves

- Conform to IEC 60898-1
- Compatible with prong-type and fork type supply busbars (except 80 A, 100 A and 125 A MCBs)
- Breaking capacity
- 10000 - IEC 60898-1 - 400 V~
- 16 kA - IEC 60947-2 - 400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries, motorised controls and add-on modules

Documentation

Catalogue pages & additional information

- Description page (p.066)
- Dimensions of din-rail equipment
- Performance of MCBs and auxiliaries

Installation & technical data

- F01204EN-01

Installation instructions & related documents

- LE03603AG

Environmental product profile

- Environnemental product sheet n°8 E0084A-FR
- LGRP-00828-V01

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.