

CAT. N° 4 093 40



MCB - DX³ 10000 - 16 KA - 4P 400 V~ - 40 A - C CURVE

Unit price ex. taxes	€98.67
Pack (number of units)	1
Volume (dm³)	0,716
Weight (g)	605,00

Product characteristics

4-pole 400 V~

- C curve
- Nominal rating I_n : 40 A
- Number of modules : 4

General characteristics

MCBs DX³ 10000 - 16 kA - thermal magnetic circuit breakers from 1 A to 125 A - B and C curves

- Conform to IEC 60898-1
- Compatible with prong-type and fork type supply busbars (except 80 A, 100 A and 125 A MCBs)
- Breaking capacity
 - 10000 - IEC 60898-1 - 400 V~
 - 16 kA - IEC 60947-2 - 400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries, motorised controls and add-on modules

Documentation



Catalogue pages & additional information

- [Description page \(p.066\)](#)
- [Technical page \(p.074-075\)](#)
- [Dimensions of din-rail equipment](#)
- [Performance of MCBs and auxiliaries](#)
- [Dimensions of din-rail equipment](#)
- [Performance of MCBs and auxiliaries](#)



Agreements & certificates of conformity

- VDE - 40034176
- OC / CB - IT - 14353
- OC / CB - IT-10652
- OC / CB - IT-10652/M2
- OC / CB - IT-10652/M1
- AENOR - 030-002269



Installation & technical data

- [F01559EN-03](#)



Environmental product profile

- [Environnemental product sheet n°8 E0112A-FR](#)