CAT. N° 4 080 93



MCB - DX³ 6000 - 10 KA - 3P 400 V~ - 40 A - D CURVE

Pack (number of units)	1
Volume (dm³)	0,716
Weight (g)	465,00

Product characteristics

3-pole 400 V~

- D curve
- Nominal rating In : 40 A
- Number of modules : 3

General characteristics

MCBs DX³ 6000 - 10 kA - thermal magnetic MCBs from 0.5 A to 63 A - D curve

- Conform to IEC 60898-1
- Compatible with both prong-type and fork type supply busbars
- Breaking capacity:
- 6000 - IEC 60898-1 - 400 V~
- 10 kA - IEC 60947-2 - 400 V~
- Can be equipped with DX³ signalling and remote tripping auxiliaries, motorised controls and add-on modules

Documentation

Catalogue pages & additional information

- Description page (p.065)
- Dimensions of din-rail equipment
- Performance of MCBs and auxiliaries

Agreements & certificates of conformity

- OC / CB-IT-10651
- OC / CB-IT-10651/M1
- AENOR-030/002268
- VDE-40034165

Installation & technical data

- F01591EN-03

Environmental product profile

- Environnemental product sheet n°8 E0112A-FR
- LGRP-00828-V01

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.