CAT. N° 4 117 91



RCD DX³-ID - 4P 400 V~ NEUTRAL RIGHT HAND SIDE - 63 A - 500 MA - A TYPE

Pack (number of units)	1
Volume (dm³)	0,701
Weight (g)	365,00

Product characteristics

4-pole - 400 V~ - neutral on right-hand side

A type

- Sensitivity : 500 mA
- In : 63 A
- Number of modules : 4

General characteristics

RCCBs - DX³-ID - residual current circuit breakers 16 A to 100 A - AC, A, F and B types

- Conform to IEC 61008 - 1, IEC 62423 (B type and F type)
- Compatible with prong-type and fork type supply busbars
- AC type : detect sinusoidal AC residual currents
- A type : detect sinusoidal AC and pulsating DC residual currents
- F type (High immunity) : detect AC and pulsating DC residual currents
- Enhanced immunity to unwanted tripping in disturbed environments
- Detection of high frequency fault currents
- B type : detect sinusoidal AC, pulsating DC and smooth DC residual currents
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls

Documentation

Catalogue pages & additional information

- Description page (p.057)
- Technical page (p.058)
- Dimensions of din-rail equipment

Installation & technical data

- F01590EN-02

Environmental product profile

- LGRP-00366-V02

Installation instructions & related documents

- LE03774AB

Agreements & certificates of conformity

- OC / CB-CB-FR_700719
- OC / CB-CB FR_705078/A1
- VDE-40032162

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.