CAT. N° 4 115 55



RCD DX³-ID - 2P 230 V~ - 40 A - 30 MA - A TYPE

Pack (number of units)	1
Volume (dm³)	0,38
Weight (g)	208,00

Product characteristics

2-pole 230 V~

A type

- Sensitivity : 30 mA
- Nominal Rating In : 40 A
- Number of modules : 2

General characteristics

RCCBs - DX³-ID - residual current circuit breakers 16 A to 100 A - AC, A, F and B types

- Conform to IEC 61008 - 1, IEC 62423 (B type and F type)
- Compatible with prong-type and fork type supply busbars
- AC type : detect sinusoidal AC residual currents
- A type : detect sinusoidal AC and pulsating DC residual currents
- F type (High immunity) : detect AC and pulsating DC residual currents
- Enhanced immunity to unwanted tripping in disturbed environments
- Detection of high frequency fault currents
- B type : detect sinusoidal AC, pulsating DC and smooth DC residual currents
- Can be equipped with DX³ signalling and remote tripping auxiliaries and motorised controls

Documentation

Catalogue pages & additional information

- Description page (p.057)
- Technical page (p.058)
- Dimensions of din-rail equipment

Installation & technical data

- F01316EN-03

Environmental product profile

- LGRP-00366-V02

Installation instructions & related documents

- LE03774AB

Agreements & certificates of conformity

- OC / CB-FR_713498
- NF-NF012_3245
- KSC-HW05019-13002B
- AENOR-030/002247
- VDE-40032162

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.