CAT. N° 4 225 59



MCCB DPX³ 1600 - S1 ELECTRONIC RELEASE - 4P - ICU 50 KA (400 V~) - IN 1000 A

Pack (number of units)	1
Volume (dm³)	47,6
Weight (g)	22 333,00

Product characteristics

MCCBs electronic release S1 fixed version

- Adjustment of Ir, Isd
- Instantaneous protection If = 20 kA
- Green indicator lamp
- Connector for test unit
- Dynamic selectivity
- 4P version: adjustment of neutral on front panel

Breaking capacity Icu 50 kA (400 V~)

- 4P
- In : 1000 A

General characteristics

DPX³ 1600 - S1 electronic release MCCBs from 630 to 1600 A

- Moulded case MCCBs for switching, control isolation and protection of low voltage electrical lines
- Can be fitted with auxiliaries
- Can be used with residual current relays
- Do not accept DPX³ electronic interface for Modbus Cat.No 4 210 75
- Supplied complete with:
  - connection plates for bars
  - insulated shields (phase barriers)
- Conform to IEC 60947-2 - Sealable adjustment
- Can be mounted on plate in XL³ cabinets and enclosures

Documentation

Catalogue pages & additional information

- Technical page (p.134-135)
- Description page (p.150)
- DPX³ 160/250/630 & 1600
- DPX³ 1600

Installation & technical data

- F01964EN01
- EXB19026_CA_DPX3_125HP250HP_630_1600EN

Installation instructions & related documents

- LE07037AB
- LE08011AA

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.