Product sheet



DMX³ 4000 LEGRAND

Equipment for conversion of a fixed device 4 poles DMX3 into draw-out device

REF. 420016 | EAN. 3245064200165

> Visit e-catalogue

Product charateristics

- DPX³ 160 thermal magnetic - MCCBs from 16 to 160 A - Can be mounted on rail or on plate in XL³ cabinets and enclosures - MCCBs for switching, control isolation and protection of low voltage electrical lines - Supplied with Fixing screws cage terminals 70 mm² max. (flexible cable) or 95 mm² max. rigid cable with Accessories - Can be fitted with DPX³ 160 and 250 common auxiliaries and Accessories - Conform to IEC 60947 - 2
- MCCBs - fixed version - Thermal adjustable from 0,8 to 1 In - Magnetic fixed at 10 In (fixed at 400 A for In 16 A and 25 A) Breaking capacity Icu 16 kA (400 V~) - 4P - In : 125 A

Documentation

TECHNICAL DOCUMENTATION

Y4220F.pdf | PDF (0.84Mo)

FT_160MT_-_FR.pdf | PDF (0.43Mo)

EXB16053_DPX3_160_250_EN.pdf | PDF (54.11Mo)

F01360EN05_DPX3_160MT_ENGv1.0.pdf | PDF (1.76Mo)

CAD & Design specs / BIM

420017.dwg | DWG (0.18Mo)

Agreements & Certificates

OC / CB-71483

LGRP-00720-V01.01-EN.pdf | PDF (1.02Mo)

OC / CB-71479

LGRP-00544-V01.01-EN.pdf | PDF (0.61Mo)