CAT. N° 4 202 48



MCCB THERMAL MAGNETIC - DPX³ 250 - ICU 36 KA 400 V~ - 4P - 200 A

Pack (number of units)	1
Volume (dm³)	3,813
Weight (g)	2 287,00

Product characteristics

MCCBs - fixed version
- Thermal adjustable from 0,8 to 1 In
- Magnetic adjustable from 5 to 10 In

Breaking capacity Icu 36 kA (400 V~)
- 4P
- In : 200 A

General characteristics

DPX³ 250 thermal magnetic - MCCBs from 100 to 250 A
- Can be mounted on rail or on plate in XL³ cabinets and enclosures
- MCCBs for switching, control isolation and protection of low voltage electrical lines
- Supplied with fixing screws, connection plates for bars and cable lugs and insulated shields (phase barriers)
- Can be fitted with cage terminals 120 mm² max. (flexible cable) or 150 mm² max. rigid cable and with DPX³ 160 and 250 common auxiliaries and accessories
- Conform to IEC 60947-2

Documentation

Installation instructions & related documents
- Y4263F

Agreements & certificates of conformity
- OC / CB-71485

Installation & technical data
- F01364EN04_DPX3250MT_ENGv1
- EXB16053_DPX3_160_250_EN

Environmental product profile
- LGRP-00733-V01
- LGRP-00570-V01

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.