## CAT. N° 4 201 24



# MCCB THERMAL MAGNETIC - DPX³ 160 - ICU 50 KA 400 V~ - 3P - 80 A

| | |
|---|---|
| Pack (number of units) | 1 |
| Volume (dm³) | 2,447 |
| Weight (g) | 1 135,00 |

## Product characteristics

**MCCBs - fixed version**
- Thermal adjustable from 0,8 to 1 In
- Magnetic fixed at 10 In (fixed at 400 A for In 16 A and 25 A)

**Breaking capacity Icu 50 kA (400 V~)**
- 3P
- In : 80 A

## General characteristics

**DPX³ 160 thermal magnetic - MCCBs from 16 to 160 A**
- Can be mounted on rail or on plate in XL³ cabinets and enclosures
- MCCBs for switching, control isolation and protection of low voltage electrical lines
- Supplied with fixing screws cage terminals 70 mm² max. (flexible cable) or 95 mm² max. rigid cable with accessories
- Can be fitted with DPX³ 160 and 250 common auxiliaries and accessories
- Conform to IEC 60947-2

## Documentation

**Catalogue pages & additional information**
- Technical page (p.074-075)
- Technical page (p.134-135)
- Description page (p.136)
- Technical page (p.137)
- Technical page (p.143)
- DPX³ 160 & 250
- DPX³ 160/250/630 & 1600

**Installation & technical data**
- F01360EN05_DPX3_160MT_ENGv1
- EXB16053_DPX3_160_250_EN

**Environmental product profile**
- LGRP-00720-V01
- LGRP-00544-V01

**Installation instructions & related documents**
- Y4220F

**Agreements & certificates of conformity**
- OC / CB-71483
- OC / CB-71479

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.