

DPX³ 250 thermal magnetic

MCCBs from 100 to 250 A



420 205



420 225



Technical characteristics and tripping curves (p. 60-62)

Dimensions (p. 55)

Can be mounted on rail 15 or on plate in XL³ cabinets and enclosures

MCCBs for switching, control isolation and protection of low voltage electrical lines

Supplied with insulated shIELDS, screw terminals 120 mm² max. (flexible cable) or 150 mm² max. rigid cable with accessories

Can be fitted with accessories and DPX³ common auxiliaires (p. 32)

Conform to IEC 60947-2

Pack	Cat.Nos		MCCBs - fixed version	
			Thermal adjustable from 0,8 to 1 In	
			Magnetic adjustable from 5 to 10 In	
			Breaking capacity Icu 25 kA (400 V~)	
	3P	4P	In (A)	
1	420 205	420 215	100	
1	420 207	420 217	160	
1	420 208	420 218	200	
1	420 209	420 219	250	
			Breaking capacity Icu 36 kA (400 V~)	
1	420 235	420 245	100	
1	420 237	420 247	160	
1	420 238	420 248	200	
1	420 239	420 249	250	
			Breaking capacity Icu 50 kA (400 V~)	
1	420 265	420 275	100	
1	420 267	420 277	160	
1	420 268	420 278	200	
1	420 269	420 279	250	
			Breaking capacity Icu 70 kA (400 V~)	
1	420 605	420 615	100	
1	420 607	420 617	160	
1	420 608	420 618	200	
1	420 609	420 619	250	

Pack	Cat.Nos		MCCBs with electronic earth leakage module - fixed version	
			Thermal adjustable from 0,8 to 1 In	
			Magnetic adjustable from 5 to 10 In	
			Equipped with earth leakage module with LCD screen	
			Adjustable sensitivity: 0.03 - 0.3 - 1 - 3 A	
			Adjustable tripping: 0 - 0.3 - 1 - 3s (with 0.03 A possible only 0s)	
			Breaking capacity Icu 25 kA (400 V~)	
	4P	In (A)		
1	420 225	100		
1	420 227	160		
1	420 228	200		
1	420 229	250		
			Breaking capacity Icu 36 kA (400 V~)	
1	420 255	100		
1	420 257	160		
1	420 258	200		
1	420 259	250		
			Breaking capacity Icu 50 kA (400 V~)	
1	420 285	100		
1	420 287	160		
1	420 288	200		
1	420 289	250		
			Breaking capacity Icu 70 kA (400 V~)	
1	420 625	100		
1	420 627	160		
1	420 628	200		
1	420 629	250		