CAT. N° 4 226 81



AUTOMATIC TRANSFER SWITCH CONTROL UNITS FOR STANDARD MANAGEMENT OF 2 CIRCUIT BREAKERS - 6 INPUTS 7 OUTPUTS

Pack (number of units)	1
Volume (dm³)	4,335
Weight (g)	604,00

Product characteristics

Automatic transfer switch control units

For standard management of 2 circuit breakers

- Configuration software available for download via e-catalogue ACU Configurator app for smartphone and tablet available on Apple Store and Google Play
- 6 programmable digital inputs and 7 programmable relay outputs
- LCD display
- IR communication port on the front panel for connection of USB or WiFi modules Cat.No 4 226 87/88
- Can be configured with the help of front panel touch keys or of the Legrand dedicated software
- Power supply: 110-240 V~
- IP40

General characteristics

Automatic transfer switch control units

- They can control transfer switching between two sources, manage generator start/stop, control single phase, two-phase and three-phase networks, control phase-phase and phase-neutral voltages
- For DPX³ and DMX³ circuit breakers and CTX³ contactors

Documentation

Installation instructions & related documents

- F02233EN02_ATS_2_SOURCES_ENG
- LE12178AA
- LE12710AA

Softwares

- Acu Configurator

Installation & technical data

- EXB17039_GT_TransferSwitching

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.