PHILIPS

Lighting



SmartBright All-in-one Solar Street Light

BRP110 LED50/757 G2 HY Solar

Integrated solar street light with Lithium Ferro Phosphate battery, solar panel and charger built into the luminaire. Independently tilt-able LED source and pole mounting bracket allows light beam to focus on road, and solar panel towards the sun. Microwave based motion sensor for optimizing battery autonomy.

Product data

General Information	
Driver included	Yes

Light Technical	
Luminous Flux	5,000 lm
Luminous Efficacy (rated) (Nom)	185 lm/W
Correlated Color Temperature (Nom)	5700 K
Color rendering index (CRI)	>70
Optical cover type	Polycarbonate

Operating and Electrical	
Power Factor (Fraction)	> 0.9
Battery type	Lithium Ferro Phosphate
Battery ampere hour	12 Ah
Battery voltage	12 V
Battery charging & discharging cycles	2000
Panel type	Mono crystalline
Panel voltage	18 V
Panel peak wattage	35 W
Charge controller type	MPPT
Charge controller wattage	27 W
Cable connection kit	Excluded
Connection	-

Temperature	
Ambient temperature range	-10 °C to 60 °C

Controls and Dimming	
Configurability	Configurable
Dimmable	Yes
Control interface	-

Mechanical and Housing	
Housing Color	RAL7040
Overall length	562 mm
Overall width	364 mm
Overall height	86 mm
Dimensions (Height x Width x Depth)	86 x 364 x 562 mm
Material	Aluminum

SmartBright All-in-one Solar Street Light


Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
CE mark	Yes
EU RoHS compliant	Yes

Over Time Performance (IEC Compliant)	
Median useful life L70B50	50,000 hour(s)

Application Conditions	
Ambient temperature range for charging	0 °C to 50 °C
Ambient temperature range for discharging (when light is on)	-10 °C to 60 °C
Solar dimming profile	First 2 Hrs - On motion : 100%, without motion :30% ; Next 3 Hrs - On motion : 60%, without motion :20% ; Next 6 Hrs On motion : 30%, without motion :10% ; Rest of the Night: On motion : 50%, without motion :30%
Grid connection type	Hybrid
Battery location	Inbuilt

Product Data	
Order product name	BRP110 LED50/757 G2 HY Solar
Full product name	BRP110 LED50/757 G2 HY Solar
Full product code	872016973546000
Order code	911401878702
Material Nr. (12NC)	911401878702
Numerator - Quantity Per Pack	1
Net Weight (Piece)	7.800 kg
EAN/UPC - Product/Case	8720169735460
Numerator - Packs per outer box	1
EAN/UPC - Case	8720169735460

Dimensional drawing



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.