Professional Multi Battery LED 360° Hybrid Work Light 12050 MH, 12000 lm, IP54

Maximum flexibility. Full compatibility with leading battery technologies.





PROFESSIONAL

brennenstuhl® MULTI BATTERY 18V-SYSTEM

AMPShare Powered by BOSCH

GERMAN INNOVATION AWARD '22 GOLD

ENGINEERED IN GERMANY

IP54 | IK08 | 5 m | HYBRID | 12000 LUMEN

Product number	1173700003
EAN	4007123681365

DESCRIPTION

- Compatible with various 18 V batteries (different Ah classes) from the 11 power tool manufacturers: Bosch Professional, Dewalt, Einhell, Fein, Festool, Flex, Hikoki, Makita, Metabo CAS, Milwaukee and Würth.
- brennenstuhl® is part of AMPShare - Powered by Bosch Professional: The AMPShare battery alliance enables the use of Brennenstuhl work lamps with the 18 V batteries from Bosch Professional.
- Work spotlight including interface adapters for 5 manufacturers (Bosch Professional, Dewalt, Makita, Metabo CAS, Milwaukee).
- More flexibility through hybrid technology: battery and mains operation possible, automatic switchover from mains to battery in case of power failure.
- With permanently installed 5 m cable (H07RN-F2X1.0).
- Very bright 360° all-round light.
- Light duration depending on the battery used 12 min per Ah.
- Battery status display for the remaining energy of the battery used, the batteries can be charged externally.
- Protection system for Power-Tool batteries: The batteries used are protected against deep discharge and overheating (caused by high load currents).
- Removable battery protection cover.
- Practical cable rewind possible and clip for fastening.
- All-round handles for easy transport.
- Includes hook for hanging with sliding mechanism to compensate for the imbalance caused by the battery in use.
- Flexible use: standing, hanging, tripod mountable.

Professional Multi Battery LED 360° Hybrid Work Light 12050 MH, 12000 lm, IP54

Maximum flexibility. Full compatibility with leading battery technologies.



Product number	1173700003
EAN	4007123681365

TECHNICAL DATA

Cable quality	Rubber-Neoprene
Luminous flux	12000 lm
Power consumption	100 W
Luminous efficacy	120 lm/W
Energy efficiency class	A to G: E
Colour temperature	6500 K
Colour rendering index	80-89 (class 1B)
Min.-Max. Nominal input voltage	220 V - 240 V
Lifetime	30000 h
Cable length	5 m
Cable designation	H07RN-F 2X1,0
Battery voltage	18 V
Impact strength	IK08
Protection class	II
Degree of protection (IP)	IP54
Colour	black/grey

PACKAGING, DIMENSIONS AND WEIGHTS

UP	1
Weight of product (without packaging)	4.98 kg
Dimension LxWxH (without packing)	28.6 cm x 28 cm x 37.8 cm
Weight of product (including packaging)	5.62 kg
Dimension LxWxH (incl. packing)	29 cm x 30 cm x 38.5 cm

SCOPE OF DELIVERY

Professional Multi Battery LED 360° Hybrid Work Light 12050 MH, 4 Interface Adapters, Bag for Adapters, 5m RN-Cable