Product sheet



XL³ LEGRAND

Modular distribution block with staggered bars 100 A - 11 connections per busbar - 6 modules

REF. 400406 | EAN. 3414971978577

> Visit e-catalogue

Product charateristics

- Input Inputer 10 - 25 mm² solid or 6 - 16 mm² stranded with or without ferrule
- 10 Output : 2 x 10 - 25 + 8 x 2.5 - 10 mm² rigid conductor
- 10 output : 2 x 6 - 16 + 8 x 1.5 - 10 mm² flexible conductor with or without ferrule
- In = 100A - 40°C Ui = 500 V
- Ipk = 26 kA - 60 ms Icw = 4,5 kA - 1s

The product's benefits

Installation

- Easy and fast cabling and connecting thanks to a maximised cabling space , optimized "orientation" of bars and adpated dimensions and positions of connections

Usage

- Transparent , removable and 180° rotating cover to adapt to all wiring situations

Avantages

- Maximised internal space and optimised bar orientation for easy cable access
- Connections sized and positioned to facilitate connection and answer all needs
- integrated system, to avoid accidental unscrewing of non connected screws

Documentation

TECHNICAL DOCUMENTATION

F03358EN-02.pdf | PDF (2.35Mo)

F03358FR-02.pdf | PDF (1.79Mo)

CATALOGUE PAGE & OTHERS

ex223001_0299.pdf | PDF (0.13Mo)