CAT. N° 0 205 57



REVERSIBLE CURVED METAL DOOR XL³ 4000 - WIDTH 975 MM - HEIGHT 2000 MM

Pack (number of units)	1
Volume (dm³)	161,538
Weight (g)	26 700,00

Product characteristics

Reversible doors
- Supplied with handle
- Interchangeable key barrels, to be ordered separately
- For mounting on front, rear or side

Curved - metal
- Width 975 mm
- Height : 2000 mm

General characteristics

Distribution enclosures XL³ 4000
- IP 30 - IK 07
- IP 55 - IK 08 with door and sealing kit for use when joining enclosures
- Consist of the combination of a "roof-base" assembly, structural uprights, functional uprights, rear and side panels RAL 7035, plinths RAL 7004
- Height 2000 or 2200 mm.
- Capacity 24 modules (enclosures width 725 or width 975 with internal cable sleeve), 36 modules (enclosures width 975)
- Usable faceplate height 1800 mm (1700 mm only if using the pivoting support frame) or 2000 mm

Documentation

Catalogue pages & additional information
- Description page (p.267)
- Selection chart (p.268)
- XL3 4000 equipment for mounting on adjustable plates

Installation & technical data
- EXB15002_CA_XL3-4000-6300_EN

Installation instructions & related documents
- F0996C-02

Agreements & certificates of conformity
- LOVAG-IT 12
- LOVAG-IT 12

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.