CAT. N° 0 205 07



ROOF BASE FOR ENCLOSURE XL³ 4000 - DEPTH 475 MM - WIDTH 975 MM

Pack (number of units)	1
Volume (dm³)	132
Weight (g)	32 465,00

Product characteristics

Enclosures and cable sleeves modular metal

Roof-base for enclosure

- Fitted with cable entry plates
- Take the structural uprights
- Depth : 475 mm
- Width external : 975 mm
- Width usable : 850 mm

General characteristics

Distribution enclosures XL³ 4000

- IP 30 - IK 07
- IP 55 - IK 08 with door and sealing kit for use when joining enclosures
- Consist of the combination of a "roof-base" assembly, structural uprights, functional uprights, rear and side panels RAL 7035, plinths RAL 7004
- Height 2000 or 2200 mm.
- Capacity 24 modules (enclosures width 725 or width 975 with internal cable sleeve), 36 modules (enclosures width 975)
- Usable faceplate height 1800 mm (1700 mm only if using the pivoting support frame) or 2000 mm

Documentation

Catalogue pages & additional information

- Description page (p.266)
- Technical page (p.267)
- Selection chart (p.268)
- XL3 4000 equipment for mounting on adjustable plates

Installation & technical data

- F00254EN-03
- EXB15002_CA_XL3-4000-6300_EN

Installation instructions & related documents

- F0998K

Agreements & certificates of conformity

- LOVAG-IT 12
- LOVAG-IT 12

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.