CAT. N° 0 522 29



BOX HYPRA - IP44/66/67-55 - FOR SURFACE MOUNTING SOCKET - 16 A - PLASTIC

Pack (number of units)	5
Volume (dm³)	3,873
Weight (g)	977,00

Product characteristics

LV 380 to 415 V~ 50/60 Hz

Accessories

- Box Hypra
- For plastic surface-mounting sockets:
- 380 to 415 V~ 16 A 3P+E
- 380 to 415 V~ 16 A 3P+N+E
- 480 to 500 V~ 16 A 3P+E
- Pack = 5

General characteristics

Hypra IP 66/67-55 plastic - increased safety - LV 16 to 125 A

- Conform to IEC 60309-1 and IEC 60309-2
- IP according to IEC 60529
- IK 09: Plastic
- Self-extinguishing: 850°C (support of active parts) / 650°C (plastic housing)

Documentation

Catalogue pages & additional information

- Selection chart (p.390-391)
- Technical page (p.392)
- Selection chart (p.393)
- Hypra

Installation & technical data

- F00138EN-03

Installation instructions & related documents

- 2500350-00

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.