



ITEM DESCRIPTION

Isolated Ground Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Smooth Face, 15 Amp, 250 Volt, Back or Side Wire, NEMA 6-15R, 2-Pole, 3-Wire, Self-Grounding - Orange

BRAND FEATURES

Leviton's line of Heavy-Duty Industrial Grade Receptacles are available with a number of wiring options and features. These heavy-duty receptacles are engineered for fine appearance and top performance in demanding commercial and institutional applications using a durable, thermoplastic face and impact-resistant construction.

UPC Code: 07847705243

Country Of Origin: Mexico

NEMA: 6-15R

QUANTITY

[ADD TO PRODUCT LIST](#)

[TECHNICAL INFORMATION](#) [SUPPORT/DOWNLOADS](#)

[AC Horsepower Ratings](#)

At Rated Voltage: 1-1/2 HP

[Electrical Specifications](#)

Grounding: Self-Grounding

Amperage: 15 A

Voltage: 250 VAC

Pole: 2

Wire: 3

Dielectric Voltage: Withstands 2000V per UL498

Current Limiting: Full Rated Current

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

[Environmental Specifications](#)

Flammability: Rated V-2 per UL 94

Operating Temperature: -40°C to 60°C

[Material Specifications](#)

Face Material: Thermoplastic Nylon

Body Material: Thermoplastic Nylon

Line Contacts: Phosphor Bronze
Terminal Screws: Plated Brass
Clamp Nuts: Galvanized Steel
Grounding Screw: Brass 8-32
Strap Material: Galvanized Steel
Isolated Ground System: Brass
Color: Orange

Mechanical Specifications

Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral
Terminal Accom.: 14-10 AWG
Product ID: Ratings are permanently marked on device
Torque Range: 14-16 inch pounds
Termination: Back or Side Wire

Product Features

NEMA: 6-15R
Termination: Back or Side Wire
Face Material: Thermoplastic Nylon
Body Material: Thermoplastic Nylon
Color: Orange
Device Type: Duplex Receptacle Outlet
Feature 4: Smooth Face
Function: Isolated Ground
Grade: Heavy-Duty Industrial Specification Grade

Standards and Certifications

NEMA: WD-6
ANSI: C-73
UL498: File E13399
UL Fed Spec WC-596: File E13399
CSA C22.2 No. 42: File 152105
NOM: 057
Warranty: 10 Year Limited