

BTICINO > Distribution and management solutions for the service sector > Hotel Room Management > Suppliers



E46ADCN

Power supply - input 230 Vac, output 27 Vdc SELV - maximum consumption 450 mA – DIN rail mounted model - space requirement 8 DIN modules – for flush mounted or wall mounted switchboards

Technical features

Height	90mm
Width	143mm
Depth	60mm
N° of modules	8
Standard reference	EN 60669-2-1EN 50491-5-1EN 50428
Rated voltage	230Vac
Rated current	0,3A
Series	MyHome

Documentation

-  [Instruction Sheet](#)
-  [DWG drawing](#)
-  [Technical guide](#)
-  [Technical guide](#)
-  [Brochure](#)
-  [Living Now english catalogue](#)

Certificazioni



We, Bticino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in Bticino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". Bticino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Related products



L4669KM1

Sheathed pair made up of 2 flexible wires with unshielded plaited sheath - insulation 300/500 V - co...



MH201

It manages scenarios related to hotel rooms (with basic time and logic conditions) - It works as a g...



336905

Specific BUS/SCS cable, unshielded, consisting of a white external sheath and 2 x 0.50 mm2 brown and...



336904

Specific BUS/SCS cable, unshielded, consisting of a white external sheath and 2 x 0.50 mm2 brown and...



L4669

Sheathed pair made up of 2 flexible wires with unshielded plaited sheath - insulation 300/500 V - co...