


F411/4

4 independent relay actuator - for single, double and combined loads: 6 A resistive and 2 A for filament lamp, 500 W for motor reducers, 2 cos? 0.5 for ferromagnetic transformers, and 70 W for fluorescent lamps - logic relay interlock via configuration - 2 DIN modules

Technical features

N° of modules	2
Rated power VA	460VA
Rated power W	460W
Rated voltage	27Vdc
Contacts	4
Rated current	0,040A
Series	MyHome

Documentation

Technical Data Sheet

DWG drawing

Technical guide

Living Now english catalogue

Certificazioni

We, Bticino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in Bticino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". Bticino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.