# WAP WTL6/1 EN

**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

## Product image



**Current and voltage transformer wiring**
Our test disconnect terminal blocks featuring spring and screw connection technology allow you to create all the important converter circuits for measuring current, voltage and power in a safe and sophisticated way.

### General ordering data

| | |
|---|---|
| Version | W-Series, End plate |
| Order No. | 1957710000 |
| Type | WAP WTL6/1 EN |
| GTIN (EAN) | 4032248654024 |
| Qty. | 20 pc(s). |

# WAP WTL6/1 EN

**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

## Technical data

### Dimensions and weights

| | | | |
|---|---|---|---|
| Depth | 34.5 mm | Depth (inches) | 1.358 inch |
| Height | 65 mm | Height (inches) | 2.559 inch |
| Width | 1.5 mm | Width (inches) | 0.059 inch |
| Net weight | 3.935 g | | |

### Temperatures

| | | | |
|---|---|---|---|
| Storage temperature | -25 °C...55 °C | Continuous operating temp., min. | -50 °C |
| Continuous operating temp., max. | 120 °C | | |

### Material data

| | | | |
|---|---|---|---|
| Material | Wemid | Colour | dark beige |
| UL 94 flammability rating | V-0 | | |

### System specifications

| | |
|---|---|
| Version | End plate |

### Additional technical data

| | |
|---|---|
| Installation advice | Feed-through (bushing),<br>Direct mounting |

### General

| | |
|---|---|
| Installation advice | Feed-through (bushing),<br>Direct mounting |

### Classifications

| | | | |
|---|---|---|---|
| ETIM 6.0 | EC000886 | ETIM 7.0 | EC000886 |
| ETIM 8.0 | EC000886 | ECLASS 9.1 | 27-14-11-33 |
| ECLASS 10.0 | 27-14-11-33 | ECLASS 11.0 | 27-14-11-33 |
| ECLASS 12.0 | 27-14-11-33 | | |

### Approvals

| | |
|---|---|
| ROHS | Conform |

### Downloads

| | |
|---|---|
| Engineering Data | CAD data – STEP |
| User Documentation | StorageConditionsTerminalBlocks |
| Catalogues | Catalogues in PDF-format |
| Brochures | |