

Hypra[®] IP 44 IK 09 -16, 32 y 63 A

Tabla de selección

■ IP 44 IK 09 -16, 32 y 63 A

Conforme a la norma IEC 60309-1 IEC 60309-2 IK 09 Autoextinguible: 850°C en partes activas según la norma IEC 60695-2-1 -50°C a +100°C BT							
			índice Horario	Toma de empotrar para gabinete	Caja de sobreponer y toma de empotrar	Clavija recta	Toma aérea
100/300 V~ 50/60 Hz	16 A	2P + T	4H	051920	051920 +052029 ⁽¹⁾	051940	051980
	32 A	2P + T	4H	051921	051921 +052940	051942	051982
200/250 V~ 50/60 Hz	16 A	2P + T	6H	052022 ⁽¹⁾	052022 ⁽¹⁾ +052029 ⁽¹⁾	052042 ⁽¹⁾	052082 ⁽¹⁾
		3P + T	9H	052023	052023 +052229 ⁽¹⁾	052043	052083
		3P + N + T	9H	052024	052024 +052229 ⁽¹⁾	052044	052084
	32 A	2P + T	6H	052718	052718 +052940	052742	052782
		3P + T	9H	052719	052719 +052940	052743	052783
		3P + N + T	9H	052720	052720 +052940	052744	052784
440/460 V~ 50/60 Hz	16 A	3P + T	11H	052310	052310 +052229 ⁽¹⁾	052311	052312
	32 A	3P + T	11H	052350	052350 +052940	052351	052352
380/415 V~ 50/60 Hz	63 A	3P + T	6H	053823	053723	053843	053883
480/500 V~ 50/60 Hz	16 A	3P + T	7H	052320	052320 +052229 ⁽¹⁾	052321	052322
	32 A	3P + T	7H	052359	052359 +052940 ⁽¹⁾	052361	052362

Nota: Todos los empaques son unitarios excepto (1).

(1) Paquete de 5.

Hypra[®] IP 44-IK 09

Clavijas rectas y tomas aéreas

■ Características técnicas

Capacidad de terminales de conexión:


Clavijas y tomas aéreas	# Conductores (flexible)	Sección nominal	
		(mm ²)	AWG
16 A	1	1 a 2,5	18 a 14
32 A	1	2,5 a 6	14 a 10
63 A	1	6 a 16	10 a 6

■ Dimensiones (mm)

Clavijas rectas

16 A


Ref. 051940, 052042/43/44, 052311/21



	Peso (kg)	A	B	C	D	Ø Cierre/amarre
16 A						
2P+T	0,150	135	100	57	55	8 a 15
3P+T	0,175	139	103	65	60	8 a 15
3P+N+T	0,210	154	118	73	66	10 a 18

32 A


Ref. 051942, 052742/43/44, 052351/61



	Peso (kg)	A	B	C	D	Ø Cierre/amarre
32 A						
2P+T	0,260	164	119	78	70,5	10 a 18
3P+T	0,175	164	119	78	70,5	12 a 22
3P+N+T	0,300	170	125	86	77	12 a 22

63 A

Ref. 053843




	Peso (kg)	Ø Cierre/amarre
63 A		
3P+T	0,640	18,5 a 29

Toma aérea IP 44

16 A


Ref. 051980, 052082/83/84, 052312/22



	Peso (kg)	A	B	C	D	Ø Cierre/Amarre
16 A						
2P+T	0,170	147	54,5	74	55	8 a 15
3P+T	0,200	151	61,5	81	60	8 a 15
3P+N+T	0,245	172	69,5	90	66	10 a 18

32 A

Ref. 051982, 052782/83/84, 052352/62



	Peso (kg)	A	B	C	D	Ø Cierre/amarre
32 A						
2P+T	0,300	177	71	93	70,5	10 a 18
3P+T	0,300	177	71	93	70,5	12 a 22
3P+N+T	0,350	183	77,5	100	77	12 a 22

Hypra[®] IP 44-IK 09


Tomas aéreas

■ Dimensiones (mm)

Toma aérea

63 A

Ref. 053883



	Peso (kg)	Ø Cierre/amarre
63 A		
3P+T	0,770	18,5 a 29

