

MENNEKES CEE plugs and connectors PowerTOP plus for use under harsh conditions

with highly heat-resistant contact carrier and nickel-plated contacts

to DIN VDE 0623, EN 60309-2, colour: grey and/or colour code. Enclosure and insert made of **AMAPLAST**.
Other voltages and frequencies available on request.

3 4 5    2p+E 3p+E 3p+N+E			Ampere	Poles	110V 50 a. 60Hz	230V 50 a. 60Hz	400V 50 a. 60Hz	500V 50 a. 60Hz						
			3p 4h	4p 4h	5p 4h	3p 6h	4p 9h	5p 9h	3p 9h	4p 6h	5p 6h	3p 7h	4p 7h	5p 7h
	Plug PowerTOP plus		63	3	3210	3212	3249		3252	3258		3255		
			63	4										
			63	5										
	⚠ IP 44 Product group 2219, type 3258 shown													
	Plug PowerTOP plus		63	3	3301	3303	3305		3308	3325		3323		
			63	4										
			63	5										
			125	3	3385*		3374*	3381*	3377*					
			125	4										
			125	5										
⚠ IP 67 Product group 2220, type 3325 shown														
	Connector PowerTOP plus with SoftCONTACT		63	3	3270	3272	3273		3275	3285		3277		
			63	4										
			63	5										
	⚠ IP 44 Product group 3219, type 3285 shown		Products with pilot contact: Part number + index P											
	Connector PowerTOP plus 63A: with SoftCONTACT 125A: with TorsionSpringCONTACT		63	3	3401	3403	3405		3408	3425		3423		
			63	4										
			63	5										
			125	3	3457*		3469*	3480*	3472*					
			125	4										
			125	5										
⚠ IP 67 Product group 3220, type 3425 shown		Products with pilot contact: Part number + index P												

*Until the PowerTOP plus are available for 125A, the reliable PowerTOP plugs and connectors are delivered with external strain relief.