CAT. N° 0 595 23



STRAIGHT PLUG HYPRA - IP66/67-55 - 380/415 V~ - 125 A - 3P+N+E

Pack (number of units)	1
Volume (dm³)	10,05
Weight (g)	1 785,00

Product characteristics

LV 380 to 415 V~ 50/60 Hz

Straight plugs

- 125 A

General characteristics

Hypra IP 66/67-55 plastic - increased safety - LV 16 to 125 A

- Conform to IEC 60309-1 and IEC 60309-2
- IP according to IEC 60529
- IK 09: Plastic
- Self-extinguishing: 850°C (support of active parts) / 650°C (plastic housing)

Documentation

Catalogue pages & additional information

- Selection chart (p.393)
- Hypra

Installation & technical data

- F00130EN-06

Installation instructions & related documents

- LE09818AA

Environmental product profile

- LGRP-00207-V01

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.