


## Panel mounted receptacle - Part no. 228A

- screw terminals
- straight



### Technical information

|                       |                 |
|-----------------------|-----------------|
| Ampere                | 16 A            |
| Poles                 | 5 p             |
| Voltage               | 400 V           |
| Earth position        | 6 h             |
| Hertz                 | 50-60 Hz        |
| Connection technology | Screw terminals |
| Contact               | standard        |
| Protection type       | IP 67           |



| Drawing<br>1 MB 141                              | Amp.<br>Poles | 16  |     |     | 32  |     |     |
|--------------------------------------------------|---------------|-----|-----|-----|-----|-----|-----|
|                                                  |               | 3   | 4   | 5   | 3   | 4   | 5   |
| Dim. in mm                                       | a             | 75  | 75  | 75  | 85  | 85  | 85  |
|                                                  | b             | 75  | 75  | 75  | 75  | 75  | 75  |
|                                                  | c             | 60  | 61  | 61  | 70  | 70  | 72  |
|                                                  | d             | 60  | 60  | 60  | 60  | 60  | 60  |
|                                                  | e             | 60  | 60  | 60  | 60  | 60  | 60  |
|                                                  | f             | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 |
|                                                  | g.            | 8   | 8   | 8   | 8   | 8   | 8   |
|                                                  | g.1           | 2   | 2   | 2   | 2   | 2   | 2   |
|                                                  | h             | 83  | 88  | 95  | 99  | 99  | 105 |
|                                                  | i             | 78  | 85  | 96  | 103 | 103 | 110 |
|                                                  | k             | 31  | 32  | 32  | 39  | 39  | 39  |
|                                                  | l             | 43  | 52  | 54  | 58  | 58  | 65  |
| Terminal for cond. cross section (mm²) min.-max. |               | 1.5 | 1.5 | 1.5 | 2.5 | 2.5 | 2.5 |
|                                                  |               | -4  | -4  | -4  | -10 | -10 | -10 |